

## Pipette rinser

## Model EPS 2D/N



Fully electronic pipette rinser with automatic rinsing agent dosing, which allows the user to freely determine all parameters of the cleaning process and thus adapt them to the degree of contamination of the pipettes. One fixed and eight freely adjustable programs ensure excellent cleaning results every time, even when requirements change. The improved editor and a four-line LCD display facilitate programming. The neutralization option is performed with commercially available citric acid.

#### **ADVANTAGES**


- Nine cleaning programs
- Operation with two types of water: demineralized and tap water
- Fully automatic program sequence
- Cleaning agent quantity adjustable
- Neutralizing agent is dosed automatically
- Cleaning temperature adjustable
- Program sequence control

**CONTROL PANEL** 

Key control panel for the input of the parameters

#### **PROGRAM SEQUENCE**

- 1. Loading of the cleaning tank with pipettes by the quiver system
- 2. Selection of the cleaning program and start of the rinsing process
- 3. Running of the cleaning program (fully automatic)
- 4. Removal of the clean and dried pipettes from the cleaning vessel



– Service button

**Program editor** 

Program status display

Program abort

#### **GEWO Feinmechanik GmbH**



# Pipette rinser

### Model EPS 2D/N

#### TECHNICAL DATA

#### **Connection values**

Current: 230 V/16 A Power: 3,0 kW

3/4"; max. 60°C inlet temperature 3/4" Tap water:

VĖ-water:

Water pressure: between 0,5 and 6 bar

Waste water: DNS0

#### **Consumption values**

low water level high water level

7 kWh 4.9 kWh Energy:

VE-water: max. 90 liters max. 130 liters Tap water: max. 180 liters max. 270 liters 0 to 400 ml 0 to 400 ml Detergent:

#### Temperature range

30°C or 96°C Cleaning:

Drying: 130°C

#### Programs for two types of water

Number:

Duration: approx. 8 hours

Capacity max. 9 quivers

Weight/material 50 kg/stainless steel housing

accessories: 8 kg

**Dimensions** 

Width: 325 mm Depth: 530 mm

Height: 920 mm (top edge of unit with closed lid)

1230 mm (with lid open) Height:



#### **ACCESSORIES INCLUDED**

6 pcs. quivers 80 x 80 x 415 mm 3 pcs. quivers 80 x 80 x 300 mm 9 pcs. numbering clips for quiver

marking

5 liters of liquid deteraent Technical documentation and

connection set

1 pc. connection set: 2x water inlet and 1x water outlet house 1x hose bow 90° 6x hose clamp 4x hose coupling

4x seal

#### PIPETTE CAPACITY

Measuring pipettes							
Volume	1,0 ml	2,0 ml	5,0 ml	10,0 ml	20,0 ml	50,0 ml	100,0 ml
Per rinser	1305	1080	810	441	324	144	54
Full pipettes							
Volume	2,0 ml	3,0 ml	5,0 ml	10,0 ml	20,0 ml	50,0 ml	100,0 ml
Per rinser	900	576	324	225	144	54	20

